MENNEKES
MY POWER CONNECTION

# Panel mounted receptacle
Part no. 1463

- screw terminals
- 20° inclination

## Technical specifications

| | |
|---|---|
| Ampere | 16 A |
| Poles | 3 p |
| Voltage | 230 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 44 |
| Flange | 73.5x64 mm |
| Fixing hole | 60x52 mm |
| Inclination | 20 ° |
| Weight | 137 g |
| Declaration of Conformity | NL,Kema, AT,ÖVE, CN,CQC |

## Drawing




| Drawing | Amp. | 16 | | | 32 | | |
|---|---|---|---|---|---|---|---|
| 1 MB 260 | Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 73.5 | 100 | 100 | 100 | 100 | 100 |
| | b | 64 | 92 | 92 | 92 | 92 | 92 |
| | c | 50 | 59 | 58 | 62 | 62 | 61 |
| | d | 60 | 85 | 85 | 85 | 85 | 85 |
| | e | 52 | 77 | 77 | 77 | 77 | 77 |
| | f | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
| | g. | 7 | 8 | 8 | 8 | 8 | 8 |
| | g.1 | 2 | 2 | 2 | 2 | 2 | 2 |
| | h | 79 | 100 | 100 | 103 | 103 | 106 |
| | k | 44 | 34 | 34 | 54 | 54 | 49 |
| | l | 52 | 55 | 65 | 67 | 67 | 72 |
| | l1 | 60 | 63 | 72 | 82 | 82 | 85 |
| | α | 20° | 20° | 20° | 20° | 20° | 20° |
| Terminal for cond. cross section (mm²) min.-max. | | 1.5 —4 | 1.5 —4 | 1.5 —4 | 2.5 —10 | 2.5 —10 | 2.5 —10 |


Subject to modificat. No liability for misprints.

MENNEKES
MY POWER CONNECTION

# Plug AM-TOP®
Part no. 248

- screw terminals
- single part body
- cable gland and sealing
- strain relief and protection against kinking

## Technical specifications

| | |
|---|---|
| Ampere | 16 A |
| Poles | 3 p |
| Voltage | 230 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | standard |
| Protection type | IP 44 |
| Weight | 131 g |
| Declaration of Conformity | DE,VDE, NL,Kema, AT,ÖVE, CN,CQC |

## Drawing




| Drawing | Amp. | 16 | | | 32 | | |
|---|---|---|---|---|---|---|---|
| 2 MB 217 | Poles | 3 | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 142 | 147 | 147 | 186 | 186 | 180 |
| | b | 53 | 59 | 67 | 70 | 70 | 77 |
| | h | 59 | 69.4 | 76 | 81 | 81 | 89.5 |
| | n | 105.2 | 110.5 | 110.5 | 141 | 141 | 135 |
| | y | 14.5 | 16 | 16 | 22 | 22 | 22 |
| Terminal for cond. cross | | 1 | 1 | 1 | 2.5 | 2.5 | 2.5 |
| section (mm²) min.-max. | | —2.5 | —2.5 | —2.5 | —6 | —6 | —6 |


Subject to modificat. No liability for misprints.