

Connector AM-TOP®

Part no. 748



- screw terminals
- with highly heat resistant contact carrier
- nickel plated contacts
- single part body
- cable gland and sealing
- strain relief and protection against kinking

Technical specifications

Ampere	32 A
Poles	7 p
Voltage	400 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	highly heat resistant contact carrier, nickel plated contacts
Protection type	IP 44
Weight	346 g
Declaration of Conformity	CN,CQC

Drawing



Drawing	Amp.	16	32
3 MB 63	Poles	7	7
Dim. in mm	a	167	208
	b	76	89
	h	98	108
	y	16	22
Terminal for cond. cross		1	2.5
section (mm ²) min.-max.		—2.5	—6

Plug AM-TOP®

Part no. 744




- screw terminals
- highly heat resistant contact carrier
- nickel plated contacts
- single part body
- cable gland and sealing
- strain relief and protection against kinking

Technical specifications

Ampere	32 A
Poles	7 p
Voltage	400 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	nickel plated contacts, highly heat resistant contact carrier
Protection type	IP 44
Weight	298 g
Declaration of Conformity	CN,CQC

Drawing



Drawing 2 MB 217	Amp. Poles	16		32	
		7	7	7	7
Dim. in mm	a	147	180		
	b	67	77		
	h	76	89.5		
	n	110.5	135		
	y	16	22		
	Terminal for cond. cross	1	2.5		
	section (mm ²) min.-max.	-2.5	-6		